



HAVE THE CONFIDENCE TO WORK SAFELY AT HEIGHTS ON BUILDING AND CONSTRUCTION SITES

Designed for **workers erecting roof truss, installing roof sheathing, shingling roofs, or installing roof bracing**. Our CoverSafe mats are lightweight and easy to manoeuvre. Constructed from aluminum the system creates a working platform that covers the ceiling members – ideal for use in timber frame house construction.



INNOVATIVE PATENTED SAFETY SOLUTIONS



ROOF SAFETY MATTING



KEY FEATURES & BENEFITS

- CoverSafe mats increase safety and productivity of workers by providing a lightweight, stable, temporary working platform
- Allows easy movement of materials and people on site increasing productivity

CoverSafe mats increase the safety and productivity of workers by providing a lightweight, stable, temporary work platform above ceiling members to prevent falls onto joists below.

Designed with adaptability in mind our mats are constructed from aluminum and are fully adjustable in width and length thanks to our XSpan technology. Easy to insert and expand from the surrounding scaffolding, set up is quick in 20 minutes and can be done by a single worker. They improve productivity when spreading the trusses out, nailing wind bracing, inspecting work and undertaking other remedial tasks. Once the work is complete the mats are easy to fold up and remove.

For Timber Frame construction, mats can be installed and fitted at ground level prior to roof being lifted into place.

Canada

- CSA S269.2-16 (reaffirmed 2021) Access scaffolding for construction purposes
- 6.2.3 Live loads on access scaffold platforms – OSC matting products comply with all three loading duties
- CSA Z797:18 National Standard of Canada (reaffirmed 2023)
- Code of practice for access scaffold – OSC matting products comply with all three loading duties

SPECIFICATION

Open size

11'0" x 2'3", covers 27'1 sq. ft.
3.6m x 0.7m, covers 2.52m²

Closed size

2'5" x 3'3" | 0.75m x 0.98m

Maximum working load

330.70 lbs maximum
150kg maximum

Weight

24.69 lbs | 11.2kg

Open sizes are typical because each mat can be adjusted to the best rectangular shape to give the optimum cover for each situation.

Training and Maintenance are offered as required.

CURRENTLY USED IN THESE SECTORS



CONSTRUCTION



DEMOLITION



REFURBISHMENT



Head Office Ontario

40 North Rivermede Road,
Units 6 - 7 Concord,
Ontario L4K 2H3

Regional Office

Alberta Office & Training Centre

Unit 107 – 7155, 57 Street SE Calgary,
Alberta T2C 5B1

Québec Office

118 - 6185 boul. Taschereau
local 180 Brossard, Québec J4Z 0E4

Tel: (905) 669 1494

Toll Free: (877) 505 5003

Web: www.keesafety.ca